



Contact Methods
Mob: (86)18668768846
Tel: (86) 577 68668118
Wechat: zigpac123
Skype: bruce.chan1999
E-mail: bruce@zigpac.com
Whatsapp: +86-18668768846
Telegram: @Zigpacstickers

Company Info
Name: Wenzhou Zigpac Industry Limited
Address: No. 148-152, Building C, Jiangbin
Commercial and Residential Building, Longgang
City, Wenzhou City, Zhejiang 325802, China



YOUR CUSTOM PRINTING & PACKAGING PARTNER FOR SMALL AND MEDIUM BUSINESSES



[illegible]

Details

[illegible][illegible][illegible]


11

1. 
2. 
3. 
4. 
5. 
6. 
7. 
8. 

[illegible][illegible]

- 000000 0000000000000000000000000000000000000000000000000
- 000000000 0000000000000000000000000000000000000000000000
- 000000000000 000000000000000000000000000000000000000000000

Mylar BoPET
BoPET^[1]
PET PET



1. 噴霧器の選択と調整

噴霧器の選択と調整は、塗料の品質と塗布の均一性を確保するために重要です。O-A-B-D-P-R-0, 6, 8-9の各モデルは、異なる用途に適した設計となっており、適切な調整を行うことで、最適な塗布結果を得ることができます。

2. 塗料の特性


塗料の特性は、塗布方法に大きく影響します。1 mmの塗膜厚を達成するために、3 mmの塗膜厚を1/8 inの塗膜厚に変換する必要があります。12の塗膜厚をOの塗膜厚に変換する必要があります。

3. 塗布条件

- 塗料の粘度と流動性を確認する
- 塗料の乾燥時間と硬化条件を確認する
- Q-1000e-C-Oの塗料特性を確認する
- 塗料の塗布速度を300%に調整する

4. 塗布結果の確認

塗布結果の確認は、塗料の品質と塗布の均一性を確保するために重要です。FAAの塗料品質基準は、FAA AC 150/5340-1M^[2]に基づいて定められており、塗料の塗布結果を確認するための重要な基準となります。



Protein Structure and Function

The protein structure is a complex of three subunits, each containing a circular domain. The subunits are connected by a central linker. The structure is shown in two views: a complete complex and a complex with one subunit detached, indicated by a red arrow.

- The protein structure is a complex of three subunits, each containing a circular domain.
- The subunits are connected by a central linker.
- The structure is shown in two views: a complete complex and a complex with one subunit detached, indicated by a red arrow.
- The detached subunit is highlighted with a red glow.

The protein structure is a complex of three subunits, each containing a circular domain. The subunits are connected by a central linker. The structure is shown in two views: a complete complex and a complex with one subunit detached, indicated by a red arrow.

Protein Structure and Function

The protein structure is a complex of three subunits, each containing a circular domain. The subunits are connected by a central linker. The structure is shown in two views: a complete complex and a complex with one subunit detached, indicated by a red arrow.

1. The protein structure is a complex of three subunits, each containing a circular domain.
2. The subunits are connected by a central linker.
3. The structure is shown in two views: a complete complex and a complex with one subunit detached, indicated by a red arrow.

4. 噴霧器噴出的噴霧應均勻地覆蓋在整個測試區域上，並應避免在測試區域外產生任何噴霧。
5. 噴霧器應在測試區域的邊緣處噴霧，以確保整個測試區域都能被均勻地覆蓋。



測試區域的定義

測試區域應為一個正方形，其邊長應為 1 英尺（304.8 毫米）。測試區域應在測試區域的邊緣處噴霧，以確保整個測試區域都能被均勻地覆蓋。

測試區域	邊長	測試區域的定義	測試區域	測試區域
測試區域	7-7.5 mil ≈ 0.18 mm	測試區域的定義	測試區域	測試區域 1 in 測試區域
測試區域	10 mil ≈ 0.25 mm	測試區域的定義	測試區域	測試區域
測試區域	14 mil ≈ 0.36 mm	測試區域的定義	測試區域	測試區域
測試區域	60 mil $\approx 1/16$ in ≈ 1.52 mm	測試區域的定義	測試區域	測試區域
測試區域	125 mil $1/8$ in ≈ 3.18 mm	測試區域的定義	測試區域	測試區域

測試區域應為一個正方形，其邊長應為 1 英尺（304.8 毫米）。測試區域應在測試區域的邊緣處噴霧，以確保整個測試區域都能被均勻地覆蓋。

ASTM ISO 測試區域的定義

ASTM D4801 測試區域

0.25 mm 0.010 in 測試區域

ASTM D4801^[5] 測試區域

測試區域

Accessibility

Accessibility is a key consideration in the design and construction of any project. It ensures that all individuals, regardless of their physical or mental abilities, can use and interact with the project. This includes providing accessible entrances, pathways, and facilities. The goal is to create an inclusive environment that meets the needs of everyone.

Signage

Signage is an essential part of any project, providing clear directions and information to users. It should be designed to be easily visible and understandable, taking into account factors such as color, font, and placement. Signage also plays a role in safety, helping to guide users and prevent accidents. The design should be consistent and professional, reflecting the overall quality of the project.



Wayfinding

Wayfinding is the process of helping people find their way through a space. It involves the use of signs, maps, and other visual cues to guide users from one location to another. Effective wayfinding systems are essential for ensuring that all users can navigate the space easily and safely.

Wayfinding is a critical component of any project, especially in large, complex environments. It helps to reduce confusion and improve the overall user experience. The design of wayfinding systems should be intuitive and easy to understand, with clear directions and consistent branding. The FAA (Federal Aviation Administration) is a key organization involved in wayfinding for airports and other transportation hubs.

Wayfinding systems should be designed to be inclusive and accessible to all users, including those with disabilities. This includes providing tactile signs and other features that can be used by people with visual impairments. The goal is to create a seamless and easy-to-navigate environment for everyone.

Wayfinding systems should also be designed to be durable and easy to maintain. This includes using materials that can withstand wear and tear and providing clear instructions for cleaning and repair. The design should be consistent and professional, reflecting the overall quality of the project.

Wayfinding systems should be designed to be flexible and adaptable to changing needs. This includes providing a system that can be easily updated and modified as the project evolves. The goal is to create a long-lasting and effective wayfinding system that meets the needs of all users.

Wayfinding systems should be designed to be user-friendly and easy to use. This includes providing clear directions and intuitive navigation tools that can be used by people of all ages and abilities. The goal is to create a seamless and easy-to-navigate environment for everyone.

Wayfinding systems should be designed to be inclusive and accessible to all users, including those with disabilities. This includes providing tactile signs and other features that can be used by people with visual impairments. The goal is to create a seamless and easy-to-navigate environment for everyone.

BoPET 60 in

1:1 PET

- AC 150/5340-1M 2019
- 6 ft ≤ 25 mph 8 ft ≥ 30 mph
- 2023 11th 1 2025
- 60 in
- ASTM D4801 0.25 mm 0.010 in
- UV 250-254 °C UV

PET

1. Science Info — Mylar BoPET
2. AC 150/5340-1M 2019-05-10 1
3. MUTCD 11th 1 2025
4. MUTCD.info — MUTCD 3 2026
5. ASTM International — D4801-08(2025) 0.25 mm 0.010 in
6. Wevolver — Mylar BoPET
7. ANSI — ISO 11469:2016
8. FHWA
9. ADA.gov
10. ADA 5